

面板安装开孔图
Panel cut out

技术参数:

- 插芯:
- 插针数: 64+PE
- 额定电流: 16A
- 额定电压: 500V
- 额定脉冲电压: 6kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V
- 绝缘阻抗: $> 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: > 500

插针:

- 接线方式: 冷压连接
- 材料: 铜合金
- 表面处理:
 - 镀银
 - 镀金
- 接触电阻: $< 1\text{m}\Omega$
- 线径范围: $0.14-4.0\text{mm}^2(26-12\text{ AWG})$
- 剥线长度: 7.5mm
- 工具:
 - 冷压钳:
 - TL02G(0.5-4mm²)
 - TL02(0.14-0.37mm²)
 - 退针器: TL01


Technical specification:

Insters:

- No. of contact: 64+PE
- Rated current: 16A
- Rated voltage: 500V
- Rated impulse voltage: 6kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V
- Insulation resistance: $> 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: > 500

Contacts:

- Terminal: crimp terminal
- Material: copper alloy
- Surface:
 - Hard-silver plated
 - Hard-gold plated
- Contact resistance: $< 1\text{m}\Omega$
- Wire gauge: $0.14-4.0\text{mm}^2(26-12\text{ AWG})$
- Stripping length: 7.5mm
- Tools:
 - Crimp contact tool:
 - TL02G(0.5-4mm²)
 - TL02(0.14-0.37mm²)
 - Contact removal tool: TL01



| | | | | | | | | | | | |
|---------------|--|----------------|--|------------------|--|-----------------|--|-------------------|--|---|--|
| | | | | 表面处理 Finish | | - | | 图号 Drawing No. | | - | |
| | | | | 材料 Material | | - | | 产品代号 Part Code | | HEE-064-FC | |
| 标记 Mark | | 处数 Number | | 变更描述/Description | | 签名 Signature | | 日期 Date | | 产品料号 Part No. | |
| | | | | | | | | | | 1230640200001 | |
| 绘图 Drawn | | 姓名/Name | | 日期/Date | | 姓名/Name | | 日期/Date | | 产品名称 Part Name | |
| 审核 Checked | | BQ LUO | | 18.10.2010 | | - | | - | | - | |
| 工艺 Process | | P RAO | | 18.10.2010 | | YY LIN | | 18.10.2010 | | - | |
| | | 批准 Approved | | | | | | | | All Dimensions in mm Original Size DIN A 4 | |
| | | | | | | | | | | 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.,LTD | |