



技术参数:

- 插芯:
- 插针数: 12/0+PE
 - 额定电流: 40A
 - 额定电压: 690V
 - 额定脉冲电压: 8kV
 - 污染等级: 3
 - 依据UL/CSA的额定电压: 600V/300V
 - 绝缘阻抗: $> 10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: > 5000
- 插针:
- 接线方式: 冷压连接
 - 材料: 铜合金
 - 表面处理: 镀金
 - 接触电阻: $< 0.3\text{m}\Omega$
 - 线径范围: 1.5-6mm²(16-10 AWG)
 - 工具:
 - 冷压钳: TL02-0G(1.5-6mm²), TL02-3G(4/6/10mm²)
 - 退针器: TL06G

Technical specification:

- Insters:
- No. of contact: 12/0+PE
 - Rated current: 40A
 - Rated voltage: 690V
 - Rated impulse voltage: 8kV
 - Pollution degree: 3
 - Rated voltage acc.to UL/CSA: 600V/300V
 - Insulation resistance: $> 10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: > 5000
- Contacts:
- Terminal: crimp terminal
 - Material: copper alloy
 - Surface: hard-gold plated
 - Contact resistance: $< 0.3\text{m}\Omega$
 - Wire gauge: 1.5-6mm²(16-10 AWG)
 - Tools:
 - Crimp contact tool: TL02-0G(1.5-6mm²), TL02-3G(4/6/10mm²)
 - Contact removal tool: TL06G

				表面处理 Finish		-		图号 Drawing No.		-	
				材料 Material		-		产品代号 Part Code		HKH-012/0-FC	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date			产品料号 Part No.		1280120200001	
绘图 Drawn	BQ LUO	姓名/Name	日期/Date	姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	
审核 Checked	P RAO		18.10.2010	-	-	2:3	V1.0	83.9g	-	-	
工艺 Process	-		-	批准 Approved	YY LIN	18.10.2010	All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		