



技术参数:

插芯:

- 插针数: 12/0+PE
- 额定电流: 40A
- 额定电压: 690V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 依据UL/CSA的额定电压: 600V/300V
- 绝缘阻抗: $> 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: > 5000

插针:

- 接线方式: 冷压连接
- 材料: 铜合金
- 表面处理: 镀金
- 接触电阻: $< 0.3\text{m}\Omega$
- 线径范围: $1.5-6\text{mm}^2(16-10\text{ AWG})$
- 工具:
 - 冷压钳:
 - TL02-0G(1.5-6mm²)
 - TL02-3G(4/6/10mm²)
 - 退针器: TL06G

Technical specification:

Insters:

- No. of contact: 12/0+PE
- Rated current: 40A
- Rated voltage: 690V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Rated voltage acc.to UL/CSA: 600V/300V
- Insulation resistance: $> 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: > 5000

Contacts:

- Terminal: crimp terminal
- Material: copper alloy
- Surface: hard-gold plated
- Contact resistance: $< 0.3\text{m}\Omega$
- Wire gauge: $1.5-6\text{mm}^2(16-10\text{ AWG})$

Tools:

- Crimp contact tool:
 - TL02-0G(1.5-6mm²)
 - TL02-3G(4/6/10mm²)
- Contact removal tool: TL06G

				表面处理 Finish		-		图号 Drawing No.		-	
				材料 Material		-		产品代号 Part Code		HKH-012/0-MC	
标记 Mark	处数 Number	变更描述/Description		签名 Signature	日期 Date			产品料号 Part No.		1280120100001	
绘图 Drawn	BQ LUO	姓名/Name	日期/Date	姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name	
审核 Checked	P RAO		18.10.2010	-	-	2:3	V1.0	74.4g	-	-	
工艺 Process	-		-	批准 Approved	YY LIN	18.10.2010	All Dimensions in mm Original Size DIN A 4		厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		