



技术参数:

- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 650A
- 接触电阻: $\leq 0.3m\Omega$
- 线径范围: 95/120/150mm²
- 最大电缆直径: 27mm
- 可插拔次数: ≥ 500
- 压力要求: 130kN

Technical specification:

- Material: copper alloy
- Surface: hard-silver plated
- Rated current: 650A
- Contact resistance: $\leq 0.3m\Omega$
- Wire gauge: 95/120/150mm²
- Max. insulation diameter: 27mm
- Mating cycles: ≥ 500
- Pressing force requirement: 130kN

产品名称/Part Name	产品料号/Part No.	D1
CHSF650-95G	1010301202002	19
CHSF650-120G	1010301202101	21
CHSF650-150G	1010301202202	23.5

标记 Mark	处数 Number	变更描述/Descriptions		签名 Signature	日期 Date	表面处理 Finish	-			图号 Drawing No.	-
绘图 Drawn	SX. HUANG	19.11.20	标准化 Stand.			材料 Material	-			产品代号 Part Code	CHSF650-XXG
审核 Checked	HZ. LAN	19.11.20				比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品料号 Part No.	-
工艺 Process				批准 Approved	HQ. ZHANG 19.11.20	1:1	V1.0	-	-	产品名称 Part Name	-
						All Dimensions in mm Original Size DIN A4			 厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD		