



技术参数:

- 材料: 铜合金
- 表面处理: 镀银
- 额定电流: 650A
- 接触电阻: $\leq 0.3m\Omega$
- 线径范围: 185/240mm²
- 最大电缆直径: 27/32mm
- 可插拔次数: ≥ 500
- 压力要求: 130kN

Technical specification:

- Material: copper alloy
- Surface: hard-silver plated
- Rated current: 650A
- Contact resistance: $\leq 0.3m\Omega$
- Wire gauge: 185/240mm²
- Max. insulation diameter: 27/32mm
- Mating cycles: ≥ 500
- Pressing force requirement: 130kN

产品名称/Part Name	产品料号/Part No.	D1
CHSF650-185G	1010301202303	21
CHSF650-240G	1010301202403	23.5

						表面处理 Finish		-		图号 Drawing No.		-		
						材料 Material		-		产品代号 Part Code		CHSF650-XXG		
标记 Mark	处数 Number	变更描述/Descriptions		签名 Signature		日期 Date				产品料号 Part No.		-		
	姓名/Name	日期/Date		姓名/Name	日期/Date	比例 Scale	版本 REV.	重量 Weight	数量 Qty.	产品名称 Part Name		-		
绘图 Drawn	SX. HUANG	19. 11. 20	标准化 Stand.			1: 1	V1. 0	-	1					
审核 Checked	HZ. LAN	19. 11. 20												
工艺 Process				批准 Approved	HQ. ZHANG	19. 11. 20			All Dimensions in mm Original Size DIN A4				厦门唯恩电气有限公司 XIAMEN WAIN ELECTRICAL CO.LTD	